



People Counting Sensor



With a detection area up to 48 m² (installed on the celling) and a 95% recognition rate, fewer sensors are needed, cutting the deployment costs for companies and organizations.

If a room is booked and yet no one shows up, the Sensor will automatically free it up. Then, the room status will be synced and updated on Yeastar Meeting Room Booking System and Yeastar Room Display, helping organizations eliminate ghost meetings and increase space utilization.

Most importantly, only counter values will be transmitted over the LoRaWAN® network, which significantly reduces privacy concerns.

- Al-powered, with accuracy rate of 95%
- Wider detection range (up to 48 m² with 16 mapped regions), and better yet, customize the detection regions according to the layout of your meeting rooms
- No facial recognition is involved in the detection process, and no image data is collected, free from privacy concerns
- Constantly detects presence and transmits headcount to Yeastar Room Display and Yeastar Meeting Room Booking System via LoRaWAN® Gateway
- Auto-releases rooms from ghost meetings and syncs the room status with Yeastar Meeting Room Booking System, increasing space utilization rate
- Equipped with Wi-Fi for Web GUI configuration

Specifications

Model	VS121-470M/868M/915M-White/Black
Protocol	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16 dBm (868 MHz)/20 dBm (915 MHz)/19 dBm (470 MHz)
Sensitivity	-137 dBm @300bps
Mode	OTAA/ABP Class C
Field of View	190 ° Horizontal, 112 ° Vertical
Recognition Range	based on a radius of 5 meters (At the height of 3m)



Advanced Custom Setting	Up to 16 mapped regions for detection
Wi-Fi	IEEE 802.11 b/g/n, 2.4GHz, only support configuration
Button	1 × Reset Button, 1 × Wi-Fi Button
LED Indicators	1 × Wi-Fi
Power Input	1 × Type-C
Power Supply	5V / 1.5A by Type-C Port
Operating Temperature	-5°C ~ +55°C
Storage Temperature	-20°C ~ +60°C
Relative Humidity	0 ~ 95% (Non-condensing)
Color	Black/White (Optional)
Dimension	85 × 85 × 20 mm (3.35 × 3.35 × 0.79 in)
Installation	Ceiling Mounting