

# E303



Anti-bacterial housing



Power over Ethernet (PoE)



Wall mounting



HD audio

## Safety that catches the eye

The E303 is a wall-mounted emergency telephone in striking traffic red. It was specifically designed for use in offices, hotel corridors, cafeterias, schools, and similar environments, enabling rapid contact in an emergency. Simply picking up the handset automatically connects the E303 to a pre-programmed number (e.g., reception, emergency services, or secretary). Its striking colour

makes it easy to spot, even for those unfamiliar with the area and in poor ambient lighting. The E303 is the ideal addition to workspaces where safety and accessibility are top priorities. Naturally, this housing is also made of antibacterial plastic.

## Basics and equipment

- Product information
  - Emergency phone | Corded handset | PN 00007040
  - Colour: traffic red
- Equipment
  - Anti-bacterial housing
  - Sturdy, solid construction
- Placement: indoor, wall mounting

## Dimensions and weight

- Dimensions (H × W × D, approx.)
  - Corded handset (on the base cradle, wall mounted): 216 mm × 53 mm × 56 mm
- Weight (approx.)
  - Corded handset (on the base cradle): 400 g

## Indicators and keys

- Corded handset: 3 LED indicators
  - Call status indication | Message waiting indication (MWI): 1 red LED
  - Mute status indication: 1 red LED
  - Speakerphone mode: 1 red LED
- Corded handset: 20 hard keys in total
  - 12 keys (standard ITU telephone keypad)
  - 4 dedicated audio keys
    - Mute (with red LED)
    - Speakerphone mode (with red LED)
    - *VOL+* → Volume +
    - *VOL-* → Volume -
  - 1 dedicated function key: Message
  - 3 programmable function keys: Speed dialling

## Audio devices and features

- Corded handset
  - Microphone
  - Handset earpiece
  - External speaker
- Hearing aid compatible (HAC)
- Built-in assignable ringtones

## Interfaces and connections

- Power options
  - [Power over Ethernet \(PoE\)](#)
    - IEEE 802.3af, class 2
- Wired interfaces
  - Telephone base
    - Network connectivity: RJ45-8P8C socket → Gigabit Ethernet (GbE)
    - Handset cord: custom socket
  - Corded handset
    - Handset cord: custom socket

## Interoperability

- Interoperable with all major IP-PBX platforms

## Administration interfaces and setup

- Configuration and setup via voice menu
- [Configuration and setup via menu-driven web user interface \(WUI\)](#)
- Advanced SIP configuration tool for easy mass deployment and phone monitoring
- [Secure Redirection And Provisioning Service \(SRAPS\)](#) support

## Networking technologies and protocols

- VLAN support
- SIP (RFC 3261)

## Call features

- 1 SIP identity / account
- Speed dialling via function keys
- Mute microphone (via dedicated function key)
- [Multicast paging](#)

## Environmental conditions

- Operating ambient temperature:
  - 5 °C - +45 °C
- Humidity (non-condensing)
  - 5 % - 95 %

## Package contents

- Hardware
  - Telephone base
  - Handset
  - Handset cord: 330 mm
  - Wall mount kit
  - 2 Ethernet cables: Cable length (approx.)  
125 mm | 2 m
- Documentation
  - [Quick Installation Guide](#)

## Snom accessories and compatible devices

- PoE injector: [A5 \(PN 00004065\)](#)

## Series overview (Special application devices)



PA1+



SP800



E303/E303A

## Disclaimer

[Further information: Snom E303 webpage](#) | [Snom Service Hub](#) | [Quick Installation Guide](#) | [User manual](#) | [Type approval](#) | [Warranty information](#) | [Company locations](#)

Snom, the names of Snom products, and Snom logos are trademarks owned by Snom Technology GmbH. All product specifications are subject to change without notification. Snom Technology GmbH reserves the right to revise and change this document at any time, without being obliged to announce such revisions or changes beforehand or after the fact. Although due care has been taken in the compilation and presentation of the information in this document, the data upon which it is based may have changed in the meantime. Snom therefore disclaims all warranties and liability for the accurateness, completeness, and currentness of the information published, except in the case of intention or gross negligence on the part of Snom or where liability arises due to binding legal provisions.